

# Construction Pine UT Structural

## Specification Sheet

CD Construction ply is an ASNZ2269 certified structural plywood. CD has one sanded face, while D face allows for some unfilled knots & splits. With a marine glue this is used in all aspects of interior construction.

## Product Info

Code	Sheet Size	Thickness	Weight	Grading
P1025	2400 x1200	7mm	10.1kg	CD
P1035	2400 x1200	9mm	12.9kg	CD
P1045	2400 x1200	12mm	17.2kg	CD
P1055	2400 x1200	15mm	21.6Kg	CD
P1075	2400 x1200	17mm	25.5kg	CD
P1095	2400 x1200	22mm	30.2Kg	CD
P1105	2400 x1200	25mm	36kg	CD

## Technical Specs

Colour	Creamy yellow to light brown
Glue Bond	A bond, Super E0
Origin	New Zealand
Environment	Plantation grown

## Ideal Uses

- Flooring
- Wall Linings
- Bracing
- General Construction

**Handling & Application /** Plywood is a natural product that can be affected by changes in weather conditions: moisture and temperature. Increased moisture content or temperature variation may cause internal stresses causing previously flat sheets to bow.

At Plymasters, precautions are taken to minimize this. However, once the plywood has left our warehouse, we cannot guarantee sheets to remain flat unless fastened. This is particularly important where free standing kitchen/cabinet doors are concerned. When storing panels, stack on a firm raised base with enough support to prevent sagging. Cover the pallet to protect top and edges.